


# Liano Junior Cleanflush™ Invisi II

4.5/3 litre Dual Flush Toilet Suite with  
Liano Junior Cleanflush™ Wall Faced Rimless  
Vitreous China Pan and Invisi II Cistern for Inwall,  
Under Counter, Induct or Inceiling applications



cleanflush



# Liano Junior Cleanflush™ Invisi II

**4.5/3 litre Dual Flush Toilet Suite with Liano Junior Cleanflush™ Vitreous China Wall Faced Rimless Pan and Invisi II Cistern for Inwall, Under Counter, Induct or Inceiling applications**



The contemporary **Liano Junior Cleanflush™** range is ideal for parents' rooms, schools and childcare facilities where hygiene is essential as children first learn to use the toilet independently. The suite comprises of the Liano Junior Cleanflush™ pan and trusted Caroma **Invisi II** cistern. The pan connection system includes the patented Caroma Uni-Orbital® Connector for increased installation flexibility. The Caroma Uni-Orbital® Connector extends to any position in a 50mm radius, unlike traditional connectors that only move backwards and forwards. The setout range is from 60mm – 120mm with a recommended setout of 90mm.

Combining universal design with rimless pan technology, the **Liano Junior Cleanflush™** is a superior flushing system suitable for domestic and commercial applications. Incorporating several patented technologies: Caroma Flow Splitter™, Caroma Flow Balancer™ and Caroma Uni-Orbital® Connector, the Cleanflush pan is innovative and the next evolution in toilets. The Flow Splitter evenly flows water around the top of the bowl to meet at the Flow Balancer which directs the water powerfully into the sump, reducing the need for brush cleaning. The rimless pan is easy to clean and unlike traditional pan profiles, provides full visibility of any grime build up. Caroma Cleanflush provides a cleaner clean for peace of mind.

- Pan:** **Liano Junior Cleanflush™** back inlet 4.5 litre full flush rimless pan
- Traps:** Universal trap for S or P-trap installations.
- Inlet:** 50mm back inlet for concealed cistern and flushvalve installation.
- Cisterns and Flushvalves:** **Invisi II** cistern – suitable for inwall, under counter, induct and inceiling applications. *For push button and access plate (supplied separately) options see chapter 6.15.1 CISTERNS of the Caroma Technical Manual.*
- Fixing:** The pan can be fixed to the floor by either bedding into mortar or using the supplied D82 Concealed Fixing Bracket.
- Seats:** The **Liano Junior** single flap soft close quick release toilet seat is provided as standard with this suite. A quality solid section compression moulded toilet seat, fitted with buffers and metal hinges.
- Colours:** White only.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

